

## Voltage Testers (continued)

UT 12 B

UT 15 B

UT 15 C



Function	UT 12 B	UT 15 B	UT 15 C
Indication	LED + buzzer	LED	LED + LCD
Voltage Measuring	90-1000VAC	12-690V AC/DC	12-690V AC/DC
Continuity Test	-	yes	yes
Phase-Sequence Test	-	yes	yes
Polarity Test	-	yes	yes
Vibrating Alarm	-	no	no

  

Part No.	Ord.No.
s UT 12 B	67518
s UT 15 B	67519
s UT 15 C	67525

SN 4



The SN-4 tester is designed for both AC and DC voltage measuring from 110 V to 400 V with frequency up to 60 Hz, detecting of a phase conductor, phase sequence of three phase system with a neutral wire and detecting polarity of DC voltage.

Part No.	Ord.No.
s SN 4	68662

SZP-1

« DIAMETRAL



Short circuit tester - acoustic and light indication  
Power Supply: 1,5V (Battery)

Part No.	Ord.No.
s SZP-1	7725

FK 01



Simple voltage tester, 110-250V AC.  
length 140mm.

Part No.	Ord.No.
s FK 01	7770

VOLTCHECK



Can be used for checking voltages from 12-250V  
With display, length 130mm

Part No.	Ord.No.
s VOLTCHECK	2303

## Special Measuring Equipments

UT 352



**Sound Level Meter**

Model UT352 is a stable, safe and reliable sound level meter. The Meter is suitable to use in noise control, quality control, health care and all different kind of environmental noise testing. For example: factory, road, family, musical instrument and all kind of places which need noise testing.

Function	UT 352
Indication	3 1/2 digit LCD (53x41mm)
Indicating range	1999
Microphone	1/2" electret microphone
Range	30 - 130 dB (A/C characteristic)
Accuracy	±1,5dB
Frequency Range	31,5 - 8000 Hz
Power supply	2x1,5V battery AA (LR06)
Dimensions	273x69x39 mm
Weight	385 g (included battery)

Part No.	Ord.No.
s UT 352	67511

LUXMETER MS-6610



MS6610 Digital Luxmeter - compact and reliable device. Separate design of photo detector and the luxmeter itself makes the measurements more convenient. Data Hold Display: LCD, 1999 counts  
**Ranges:** 0-2000 Lux ±5%, 2000-19990 Lux ±5%, 20000-50000 Lux ±5%  
**Power supply:** 9V battery  
**Measuring rate:** 2/sec.  
**Accessories:** battery, protective case

**Dimensions:**  
 luxmeter 126x72x27mm  
 sensor 83x52x21mm

Part No.	Ord.No.
s LUXMETER MS-6610	52889

VA 6450



**Ultrasonic Distance Meter**

- Measure distance, height, area, volume fast and easily
- Measurement range: 0.6~15m
- Accuracy: ±0.5%±2digit
- Resolution: 0.01m
- Aperture angle: Approx.±5°
- Laser type: 630 ~ 650nm
- Laser power: =1mW
- Laser class: class II(US version)

Function	VA 6450
Indicating range	0,6 - 15m
Accuracy	±0,5 % ±1 digit
Resolution	0,01m
Aperture angle	approx ±5°
Laser type	630 - 650 nm
Laser power	≤1mW
Battery	9V 6F22
Dimensions	130x50x30mm
Weight	cca 150g

Part No.	Ord.No.
s VA 6450	59379