

## Other Tweeters

PT1-1010



piezo	
<b>Technical Parameters</b>	<b>PT1-1010</b>
Dimensions	85 x 85 mm
Depth	75 mm
Frequency Range	4-40 KHz
Sensitivity	105 dB
<b>Part No.</b>	<b>Ord.No.</b>
s PT1-1010	47893

PT1-1012



piezo	
<b>Technical Parameters</b>	<b>PT1-1012</b>
Dimensions	145 x 70 mm
Depth	54 mm
Frequency Range	3,5-40 KHz
Sensitivity	96 dB
<b>Part No.</b>	<b>Ord.No.</b>
s PT1-1012	52454

PT1-1016



piezo	
<b>Technical Parameters</b>	<b>PT1-1016</b>
Dimensions	186 x 80 mm
Depth	105 mm
Frequency Range	1-20 KHz
Sensitivity	110 dB
<b>Part No.</b>	<b>Ord.No.</b>
s PT1-1016	52453

COP-35A



<b>Technical Parameters</b>	<b>COP-35A</b>
Dimensions	D100x70 mm
Depth	50 mm
Power	30 W
Impedance	5,5 Ω
Frequency Range	0,8-18 KHz
Sensitivity	103 dB
<b>Part No.</b>	<b>Ord.No.</b>
s COP-35A	52262

PT25B-1



<b>Technical Parameters</b>	<b>PT25B-1</b>
Dimensions	99x99x80 mm
Depth	72 mm
Power	150 W
Impedance	4 Ω
Frequency Range	3-22 KHz
Sensitivity	96 dB
<b>Part No.</b>	<b>Ord.No.</b>
s PT25B-1	47277

MYLAR QUADRO/8



callote	
<b>Technical Parameters</b>	<b>Mylar Quadro/8</b>
Dimensions	61x61 mm
Depth	22 mm
Power	80 W
Impedance	8 Ω
Frequency Range	3-20 KHz
Sensitivity	88 dB
<b>Part No.</b>	<b>Ord.No.</b>
s Mylar Quadro/8	47557

MYLAR RONDO/8



callote	
<b>Technical Parameters</b>	<b>Mylar Rondo/8</b>
Dimensions	71 mm
Depth	22 mm
Power	80 W
Impedance	8 Ω
Frequency Range	3-20 KHz
Sensitivity	88 dB
<b>Part No.</b>	<b>Ord.No.</b>
s Mylar Rondo/8	47558