

Typical Usage	Target Gas	Heater Voltage	Heater Power Consumption	Type	Features	Detection Range
Home gas leak detector	Methane/Propane/Hydrogen	5V DC	400mW	SP-11-00		300 to 10 000ppm
	Methane/Propane/Hydrogen	5V DC	400mW	SP-12A-00	High Siloxane resistant	300 to 10 000ppm
	Propane	5V DC	400mW	SP-15A-00	High Siloxane resistant	300 to 10 000ppm
Industrial gas leak detector	Hydrogen	5V DC	400mW	SP-19-01	High Sensitivity	10 to 2 000ppm
	VOC/Alcohol	5V DC	400mW	SP-31-00		10 to 1 000ppm
	Refrigerant/Freon (R22)	5V DC	400mW	SP-41-00		10 to 3 000ppm
	Refrigerant/Freon (R134a, R407A etc.)	5V DC	400mW	SP-42A-00		10 to 300ppm
	Various Freon (R410A, R404A, R32 etc.)	5V DC	400mW	SP-42AF-00	High Siloxane resistant	100 to 10 000ppm
	Ammonia	5V DC	400mW	SP-53B-00		1 to 3 000ppm
Air quality control	Carbon monoxide/VOC/Alcohol	5V DC	400mW	SP3S-AQ2-01		1 to 100ppm
	Ozone	5V DC	400mW	SP3-61-00		0.025 to 0.55ppm